

# Crossply

## 10" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.0/16.0-10	6.0 - 7.0	6	20	1.4	16.00	407	6.50	166	5.90	151	1258	782
7.0/16.0-10	7.0 - 8.0	7	20	1.4	15.90	404	7.50	190	6.80	172	1268	788
8.5/16.0-10	8.5 - 9.5	9	20	1.4	15.90	403	9.25	235	8.00	203	1268	792

## 13" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.0/19.5-13	5.5 - 6.5	6	20	1.36	19.35	491	6.60	168	6.10	154	1042	651
6.5/19.5-13	5.5 - 7.0	6	20	1.36	19.25	488	6.80	173	6.30	160	1048	655
7.0/19.5-13	5.5 - 8.0	6	20	1.36	19.30	490	7.10	180	6.90	175	1045	653
7.5/19.5-13	6.0 - 8.5	6	20	1.36	18.90	480	8.60	218	7.60	193	1067	667
8.0/19.5-13	7.0 - 9.0	8	20	1.36	19.30	490	8.70	221	7.90	200	1045	653
8.5/19.5-13	8.0 - 10.0	8	20	1.36	19.60	497	8.90	226	8.00	203	1029	643
9.0/19.5-13	9.0 - 11.0	9	20	1.36	19.90	505	10.50	267	9.30	236	1013	633
6.2/20.0-13	5.5 - 6.5	6	20	1.36	19.90	505	7.20	183	6.10	154	1013	633
6.5/20.0-13	5.5 - 7.0	6	20	1.36	20.10	510	7.30	185	6.50	165	1003	627
7.0/20.0-13	6.0 - 8.0	7	20	1.36	20.10	510	8.00	203	7.40	187	1003	627
7.2/20.0-13	6.0 - 8.0	8	20	1.36	20.20	513	9.00	229	7.10	180	998	624
7.5/20.0-13	6.5 - 8.5	8	20	1.36	20.25	514	9.00	229	7.70	195	996	622
8.2/20.0-13	7.0 - 9.0	9	20	1.36	19.95	506	9.75	248	8.50	215	1011	632
9.0/20.0-13	8.0 - 10.0	10	20	1.36	20.00	508	10.65	271	9.20	233	1008	630
10.0/20.0-13	9.0 - 11.0	10	20	1.36	19.80	502	11.10	282	10.20	259	1018	636
6.0/21.0-13	5.5 - 7.0	6	20	1.36	20.50	520	7.40	188	6.20	157	984	615
6.5/21.0-13	5.5 - 7.5	7	20	1.36	20.50	520	9.00	229	6.50	165	984	615
7.0/21.0-13	6.0 - 8.0	8	20	1.36	20.60	523	9.00	229	7.20	182	979	612
7.5/21.0-13	6.5 - 8.5	8	20	1.36	20.50	520	8.50	216	7.40	187	984	615
8.0/21.0-13	7.0 - 9.0	9	20	1.4	20.80	528	9.90	252	8.10	206	969	602
8.5/21.0-13	7.5 - 9.0	9	20	1.36	20.80	528	10.20	259	8.50	215	969	606
9.0/21.0-13	8.0 - 10.0	10	20	1.36	21.00	533	10.90	277	9.10	231	960	600
7.0/22.0-13	6.5 - 8.5	7.5	20	1.36	21.60	548	8.70	221	6.90	175	934	584
8.2/22.0-13	7.0 - 10.0	9	20	1.36	22.00	558	10.10	257	8.60	218	917	573
9.2/22.0-13	8.5 - 10.5	10	20	1.36	22.40	568	11.10	282	9.10	231	900	562
10.0/22.0-13	9.0 - 12.0	11	20	1.36	22.10	561	11.90	302	10.30	261	912	570
10.5/23.0-13	9.5 - 11.5	11	20	1.36	23.50	596	12.30	312	10.30	261	858	536
12.0/23.0-13	12.0 - 14.0	13	20	1.36	23.20	589	14.50	368	12.30	312	869	543
13.0/23.0-13	13.0 - 15.0	14	20	1.36	23.25	590	15.15	385	13.00	330	867	542
14.0/23.0-13	14.0 - 15.0	14	20	1.36	23.25	590	15.55	395	13.60	345	867	542
13.0/24.5-13	13.0 - 15.0	14	20	1.36	24.30	617	15.50	394	12.50	317	830	519
15.0/26.0-13	15.0 - 18.0	16	20	1.36	25.75	654	17.75	451	15.00	381	783	489
16.2/26.0-13	16.0 - 18.0	17	20	1.36	25.80	655	18.75	476	16.30	414	782	489

**14" Diameter**

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.6/19.5-14	5.5 - 7.5	6	30	2.04	20.00	508	7.20	183	6.80	172	1008	630
6.5/21.0-14	5.5 - 7.0	6	20	1.36	21.40	543	7.25	184	7.60	193	942	589
7.0/21.0-14	5.5 - 8.0	7	20	1.36	21.00	533	7.30	185	7.90	200	960	600
7.0/21.5-14	5.5 - 6.0	5.5	20	1.36	21.90	556	7.75	197	7.00	177	921	576

**15" Diameter**

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
7.0/21.5-15	5.5 - 7.5	6	30	2.04	22.10	561	7.40	188	7.00	177	912	570
7.5/21.5-15	6.0 - 8.0	6	30	2.04	22.20	563	7.80	198	7.20	182	908	568
8.0/21.5-15	6.5 - 8.5	7.5	30	2.04	21.80	553	8.80	224	7.80	198	925	578
8.7/21.5-15	7.5 - 9.0	8	30	2.04	22.10	561	9.70	246	8.40	213	912	570
9.5/21.5-15	8.0 - 10.0	10	30	2.04	21.85	554	10.65	271	9.50	241	923	577
10.0/21.5-15	8.5 - 11.0	10	30	2.04	21.85	554	11.00	279	10.00	254	923	577
10.7/21.5-15	9.0 - 11.0	10	30	2.04	21.85	554	11.30	287	10.60	269	923	577
8.0/22.5-15	6.5 - 7.5	7	30	2.04	22.45	570	8.95	227	7.75	196	898	561
6.5/23.0-15	6.0 - 7.5	6	30	2.04	23.00	584	7.55	192	6.50	165	877	548
7.0/23.0-15	6.5 - 8.0	7	30	2.04	23.10	586	7.95	202	6.90	175	873	546
7.5/23.0-15	7.0 - 8.5	8	30	2.04	22.80	579	8.50	216	7.40	187	884	552
10.5/23.0-15	10.0 - 12.0	11	30	2.04	23.55	598	11.95	304	10.30	261	856	535
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534
9.0/23.5-15	7.0 - 10.0	8.5	30	2.04	23.60	599	9.90	251	9.30	236	854	534
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535
11.0/23.5-15	10.0 - 12.0	11	30	2.04	23.30	591	12.10	307	11.30	287	865	541
12.5/23.5-15	11.0 - 13.5	12	30	2.04	23.30	591	13.30	338	12.70	322	865	541
9.0/25.0-15	9.0 - 11.0	10	30	2.1	24.75	629	10.10	257	8.90	226	815	506
9.5/25.0-15	9.0 - 11.0	10	30	2.04	24.75	628	11.70	297	9.25	234	815	509
11.0/25.0-15	10.0 - 12.0	12	30	2.04	24.70	627	13.60	345	11.30	287	816	510
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489
16.2/26.0-15	16.0 - 18.0	16	30	2.04	25.80	655	17.90	455	16.30	414	782	489
12.5/27.0-15	11.5 - 14.5	13	30	2.04	27.00	685	15.25	387	12.50	317	747	467
14.0/27.0-15	13.0 - 16.0	15	30	2.04	27.10	688	16.70	424	14.00	355	744	465
16.0/27.0-15	15.0 - 18.0	16	30	2.04	27.50	698	16.80	427	16.10	408	733	458

**16" Diameter**

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
9.5/21.5-16	8.0 - 10.0	10	30	2.04	21.85	554	10.30	262	9.50	241	923	577
10.0/21.5-16	8.5 - 11.0	10	30	2.04	22.10	561	10.75	273	10.00	254	912	570
10.7/21.5-16	9.0 - 11.0	11	30	2.04	22.05	560	11.60	295	10.60	269	915	572
7.5/22.5-16	6.0 - 7.0	6	30	2.04	22.65	575	7.65	194	7.30	185	890	556
8.0/22.5-16	6.5 - 7.5	7	30	2.04	22.65	575	8.55	217	7.90	200	890	556
7.0/23.0-16	5.5 - 7.0	6	20	1.36	23.70	601	7.40	188	7.00	177	851	532
7.5/23.0-16	6.0 - 8.0	7.5	20	1.36	23.80	604	8.45	215	7.50	190	847	529
8.5/23.3-16	7.5 - 8.0	8	30	2.04	23.55	598	9.60	244	8.80	223	856	535
9.0/23.3-16	8.0 - 9.0	8	30	2.04	23.70	601	9.90	251	9.30	236	851	532
8.0/23.5-16	7.0 - 9.0	8	30	2.04	23.70	601	9.00	229	7.80	198	851	532
8.5/23.5-16	7.5 - 9.5	7.5	30	2.04	23.60	599	8.90	226	8.50	215	854	534
9.0/23.5-16	8.0 - 10.0	8.5	30	2.04	23.60	599	9.50	241	9.30	236	854	534
9.5/23.5-16	8.5 - 10.5	8.5	30	2.04	23.60	599	9.80	249	9.50	241	854	534
10.0/23.5-16	9.0 - 11.0	10	30	2.04	23.60	599	10.95	278	10.00	254	854	534
10.5/23.5-16	10.0 - 11.5	11	30	2.04	23.60	599	11.80	300	10.45	265	854	534
11.0/23.5-16	10.0 - 12.0	12	30	2.04	23.50	596	12.55	319	11.30	287	858	536
11.7/23.5-16	10.5 - 12.5	12.5	30	2.04	23.50	596	13.00	330	12.00	304	858	536
12.5/23.5-16	11.5 - 13.5	13.5	30	2.04	23.40	594	13.75	349	12.70	322	862	539
11.0/25.0-16	10.0 - 12.0	12	30	2.04	24.75	628	13.30	338	11.30	287	815	509
12.5/25.0-16	11.5 - 13.5	13	30	2.04	24.75	628	14.20	361	12.50	317	815	509
13.5/25.0-16	12.0 - 14.5	14	30	2.04	25.00	635	15.20	386	13.40	340	807	504
14.0/27.0-16	13.0 - 16.0	14	30	2.04	27.20	690	15.75	400	14.00	355	741	463

**17" Diameter**

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
7.0/24.0-17	6.5 - 7.5	7.5	30	2.1	24.60	624	8.98	228	7.17	182	816	510
7.5/24.0-17	7.0 - 8.0	8	30	2.1	24.30	618	9.05	230	7.70	195	824	515
8.0/24.0-17	7.5 - 8.5	8	30	2.1	24.50	622	9.45	240	8.07	205	818	512
8.0/25.0-17	8.0 - 9.0	8	20	1.36	25.20	640	9.00	229	8.00	203	800	500
9.0/25.0-17	8.0 - 10.0	8.5	30	2.04	25.15	638	9.80	249	8.50	215	802	501