

Crossply

10" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.0/16.0-10	6.0 - 7.0	6	20	1.4	16.00	407	6.50	166	5.90	151	1258	782
7.0/16.0-10	7.0 - 8.0	7	20	1.4	15.90	404	7.50	190	6.80	172	1268	788
8.5/16.0-10	8.5 - 9.5	9	20	1.4	15.90	403	9.25	235	8.00	203	1268	792

13" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.0/19.5-13	5.5 - 6.5	6	20	1.36	19.35	491	6.60	168	6.10	154	1042	651
6.5/19.5-13	5.5 - 7.0	6	20	1.36	19.25	488	6.80	173	6.30	160	1048	655
7.0/19.5-13	5.5 - 8.0	6	20	1.36	19.30	490	7.10	180	6.90	175	1045	653
7.5/19.5-13	6.0 - 8.5	6	20	1.36	18.90	480	8.60	218	7.60	193	1067	667
8.0/19.5-13	7.0 - 9.0	8	20	1.36	19.30	490	8.70	221	7.90	200	1045	653
8.5/19.5-13	8.0 - 10.0	8	20	1.36	19.60	497	8.90	226	8.00	203	1029	643
9.0/19.5-13	9.0 - 11.0	9	20	1.36	19.90	505	10.50	267	9.30	236	1013	633
6.2/20.0-13	5.5 - 6.5	6	20	1.36	19.90	505	7.20	183	6.10	154	1013	633
6.5/20.0-13	5.5 - 7.0	6	20	1.36	20.10	510	7.30	185	6.50	165	1003	627
7.0/20.0-13	6.0 - 8.0	7	20	1.36	20.10	510	8.00	203	7.40	187	1003	627
7.2/20.0-13	6.0 - 8.0	8	20	1.36	20.20	513	9.00	229	7.10	180	998	624
7.5/20.0-13	6.5 - 8.5	8	20	1.36	20.25	514	9.00	229	7.70	195	996	622
8.2/20.0-13	7.0 - 9.0	9	20	1.36	19.95	506	9.75	248	8.50	215	1011	632
9.0/20.0-13	8.0 - 10.0	10	20	1.36	20.00	508	10.65	271	9.20	233	1008	630
10.0/20.0-13	9.0 - 11.0	10	20	1.36	19.80	502	11.10	282	10.20	259	1018	636
6.0/21.0-13	5.5 - 7.0	6	20	1.36	20.50	520	7.40	188	6.20	157	984	615
6.5/21.0-13	5.5 - 7.5	7	20	1.36	20.50	520	9.00	229	6.50	165	984	615
7.0/21.0-13	6.0 - 8.0	8	20	1.36	20.60	523	9.00	229	7.20	182	979	612
7.5/21.0-13	6.5 - 8.5	8	20	1.36	20.50	520	8.50	216	7.40	187	984	615
8.0/21.0-13	7.0 - 9.0	9	20	1.4	20.80	528	9.90	252	8.10	206	969	602
8.5/21.0-13	7.5 - 9.0	9	20	1.36	20.80	528	10.20	259	8.50	215	969	606
9.0/21.0-13	8.0 - 10.0	10	20	1.36	21.00	533	10.90	277	9.10	231	960	600
7.0/22.0-13	6.5 - 8.5	7.5	20	1.36	21.60	548	8.70	221	6.90	175	934	584
8.2/22.0-13	7.0 - 10.0	9	20	1.36	22.00	558	10.10	257	8.60	218	917	573
9.2/22.0-13	8.5 - 10.5	10	20	1.36	22.40	568	11.10	282	9.10	231	900	562
10.0/22.0-13	9.0 - 12.0	11	20	1.36	22.10	561	11.90	302	10.30	261	912	570
10.5/23.0-13	9.5 - 11.5	11	20	1.36	23.50	596	12.30	312	10.30	261	858	536
12.0/23.0-13	12.0 - 14.0	13	20	1.36	23.20	589	14.50	368	12.30	312	869	543
13.0/23.0-13	13.0 - 15.0	14	20	1.36	23.25	590	15.15	385	13.00	330	867	542
14.0/23.0-13	14.0 - 15.0	14	20	1.36	23.25	590	15.55	395	13.60	345	867	542
13.0/24.5-13	13.0 - 15.0	14	20	1.36	24.30	617	15.50	394	12.50	317	830	519
15.0/26.0-13	15.0 - 18.0	16	20	1.36	25.75	654	17.75	451	15.00	381	783	489
16.2/26.0-13	16.0 - 18.0	17	20	1.36	25.80	655	18.75	476	16.30	414	782	489

14" Diameter												
Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
6.6/19.5-14	5.5 - 7.5	6	30	2.04	20.00	508	7.20	183	6.80	172	1008	630
6.5/21.0-14	5.5 - 7.0	6	20	1.36	21.40	543	7.25	184	7.60	193	942	589
7.0/21.0-14	5.5 - 8.0	7	20	1.36	21.00	533	7.30	185	7.90	200	960	600
7.0/21.5-14	5.5 - 6.0	5.5	20	1.36	21.90	556	7.75	197	7.00	177	921	576
15" Diameter												
Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
7.0/21.5-15	5.5 - 7.5	6	30	2.04	22.10	561	7.40	188	7.00	177	912	570
7.5/21.5-15	6.0 - 8.0	6	30	2.04	22.20	563	7.80	198	7.20	182	908	568
8.0/21.5-15	6.5 - 8.5	7.5	30	2.04	21.80	553	8.80	224	7.80	198	925	578
8.7/21.5-15	7.5 - 9.0	8	30	2.04	22.10	561	9.70	246	8.40	213	912	570
9.5/21.5-15	8.0 - 10.0	10	30	2.04	21.85	554	10.65	271	9.50	241	923	577
10.0/21.5-15	8.5 - 11.0	10	30	2.04	21.85	554	11.00	279	10.00	254	923	577
10.7/21.5-15	9.0 - 11.0	10	30	2.04	21.85	554	11.30	287	10.60	269	923	577
8.0/22.5-15	6.5 - 7.5	7	30	2.04	22.45	570	8.95	227	7.75	196	898	561
6.5/23.0-15	6.0 - 7.5	6	30	2.04	23.00	584	7.55	192	6.50	165	877	548
7.0/23.0-15	6.5 - 8.0	7	30	2.04	23.10	586	7.95	202	6.90	175	873	546
7.5/23.0-15	7.0 - 8.5	8	30	2.04	22.80	579	8.50	216	7.40	187	884	552
10.5/23.0-15	10.0 - 12.0	11	30	2.04	23.55	598	11.95	304	10.30	261	856	535
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534
9.0/23.5-15	7.0 - 10.0	8.5	30	2.04	23.60	599	9.90	251	9.30	236	854	534
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535
11.0/23.5-15	10.0 - 12.0	11	30	2.04	23.30	591	12.10	307	11.30	287	865	541
12.5/23.5-15	11.0 - 13.5	12	30	2.04	23.30	591	13.30	338	12.70	322	865	541
9.0/25.0-15	9.0 - 11.0	10	30	2.1	24.75	629	10.10	257	8.90	226	815	506
9.5/25.0-15	9.0 - 11.0	10	30	2.04	24.75	628	11.70	297	9.25	234	815	509
11.0/25.0-15	10.0 - 12.0	12	30	2.04	24.70	627	13.60	345	11.30	287	816	510
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489
16.2/26.0-15	16.0 - 18.0	16	30	2.04	25.80	655	17.90	455	16.30	414	782	489
12.5/27.0-15	11.5 - 14.5	13	30	2.04	27.00	685	15.25	387	12.50	317	747	467
14.0/27.0-15	13.0 - 16.0	15	30	2.04	27.10	688	16.70	424	14.00	355	744	465
16.0/27.0-15	15.0 - 18.0	16	30	2.04	27.50	698	16.80	427	16.10	408	733	458

16" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
9.5/21.5-16	8.0 - 10.0	10	30	2.04	21.85	554	10.30	262	9.50	241	923	577
10.0/21.5-16	8.5 - 11.0	10	30	2.04	22.10	561	10.75	273	10.00	254	912	570
10.7/21.5-16	9.0 - 11.0	11	30	2.04	22.05	560	11.60	295	10.60	269	915	572
7.5/22.5-16	6.0 - 7.0	6	30	2.04	22.65	575	7.65	194	7.30	185	890	556
8.0/22.5-16	6.5 - 7.5	7	30	2.04	22.65	575	8.55	217	7.90	200	890	556
7.0/23.0-16	5.5 - 7.0	6	20	1.36	23.70	601	7.40	188	7.00	177	851	532
7.5/23.0-16	6.0 - 8.0	7.5	20	1.36	23.80	604	8.45	215	7.50	190	847	529
8.5/23.3-16	7.5 - 8.0	8	30	2.04	23.55	598	9.60	244	8.80	223	856	535
9.0/23.3-16	8.0 - 9.0	8	30	2.04	23.70	601	9.90	251	9.30	236	851	532
8.0/23.5-16	7.0 - 9.0	8	30	2.04	23.70	601	9.00	229	7.80	198	851	532
8.5/23.5-16	7.5 - 9.5	7.5	30	2.04	23.60	599	8.90	226	8.50	215	854	534
9.0/23.5-16	8.0 - 10.0	8.5	30	2.04	23.60	599	9.50	241	9.30	236	854	534
9.5/23.5-16	8.5 - 10.5	8.5	30	2.04	23.60	599	9.80	249	9.50	241	854	534
10.0/23.5-16	9.0 - 11.0	10	30	2.04	23.60	599	10.95	278	10.00	254	854	534
10.5/23.5-16	10.0 - 11.5	11	30	2.04	23.60	599	11.80	300	10.45	265	854	534
11.0/23.5-16	10.0 - 12.0	12	30	2.04	23.50	596	12.55	319	11.30	287	858	536
11.7/23.5-16	10.5 - 12.5	12.5	30	2.04	23.50	596	13.00	330	12.00	304	858	536
12.5/23.5-16	11.5 - 13.5	13.5	30	2.04	23.40	594	13.75	349	12.70	322	862	539
11.0/25.0-16	10.0 - 12.0	12	30	2.04	24.75	628	13.30	338	11.30	287	815	509
12.5/25.0-16	11.5 - 13.5	13	30	2.04	24.75	628	14.20	361	12.50	317	815	509
13.5/25.0-16	12.0 - 14.5	14	30	2.04	25.00	635	15.20	386	13.40	340	807	504
14.0/27.0-16	13.0 - 16.0	14	30	2.04	27.20	690	15.75	400	14.00	355	741	463

17" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
7.0/24.0-17	6.5 - 7.5	7.5	30	2.1	24.60	624	8.98	228	7.17	182	816	510
7.5/24.0-17	7.0 - 8.0	8	30	2.1	24.30	618	9.05	230	7.70	195	824	515
8.0/24.0-17	7.5 - 8.5	8	30	2.1	24.50	622	9.45	240	8.07	205	818	512
8.0/25.0-17	8.0 - 9.0	8	20	1.36	25.20	640	9.00	229	8.00	203	800	500
9.0/25.0-17	8.0 - 10.0	8.5	30	2.04	25.15	638	9.80	249	8.50	215	802	501