

## Radial

### 13" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
160/530R13	5.5 - 7.0	6	20	1.4	20.90	531	7.40	188	6.25	159	965	600
175/530R13	7.0 - 8.0	7.5	20	1.4	20.80	528	9.00	229	7.90	201	969	602
195/530R13	8.0 - 9.0	8.5	20	1.4	20.80	528	10.00	254	8.90	226	969	602
200/530R13	8.0 - 10.0	9	20	1.4	21.20	538	9.60	244	8.00	203	951	595
180/550R13	8.5 - 9.5	9	20	1.4	21.80	554	9.50	241	7.25	184	925	575
210/550R13	9.0 - 10.0	10	20	1.4	21.80	554	10.60	269	8.25	210	925	575
230/550R13	9.0 - 11.0	10	20	1.4	21.80	554	11.40	290	9.20	234	925	575
250/570R13	10.0 - 11.0	10	20	1.4	22.60	574	11.40	290	9.70	246	892	558
275/570R13	10.5 - 12.0	11	20	1.4	22.70	577	12.40	315	10.80	275	888	552
290/570R13	10.5 - 12.0	11.75	20	1.4	22.80	579	12.48	317	11.10	282	884	550
225/600R13	10.0 - 11.0	10.5	20	1.4	23.75	603	11.26	286	8.25	210	849	528
240/600R13	10.0 - 11.0	10	20	1.4	24.09	612	11.26	286	9.49	241	837	520
245/600R13	10.0 - 11.0	10	20	1.4	23.62	600	11.30	287	9.57	243	854	531
300/600R13	13.0 - 14.0	13	20	1.4	23.90	607	14.65	372	11.85	301	844	524
330/620R13	14.0 - 16.0	15	20	1.4	24.45	621	15.90	404	13.50	343	825	515
245/635R13	11.0 - 12.5	11.75	20	1.4	25.20	640	12.56	319	9.50	241	800	500
245/640R13	11.0 - 12.5	11.75	20	1.4	25.10	638	12.20	310	10.00	255	803	499
270/660R13	11.0 - 12.5	11.75	20	1.4	25.70	652	13.40	340	11.10	281	785	488
315/660R13	13.0 - 15.0	13.75	20	1.4	25.75	654	15.00	381	12.25	311	783	487
350/660R13	14.0 - 16.0	15	20	1.4	25.70	652	16.90	428	14.60	370	785	488
370/660R13	14.0 - 16.0	15	20	1.4	25.75	654	17.00	432	15.00	381	783	487

### 14" Diameter

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
170/550R14	5.5 - 6.5	6	20	1.4	21.80	554	7.40	188	6.50	165	925	578

<b>15" Diameter</b>												
Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
185/550R15	5.5-6.5	6	29	2	21.70	550	7.60	193	7.40	187	931	579
210/550R15	8.0-10.0	8.5	26	1.8	21.90	555	9.50	241	8.70	220	923	574
230/550R15	8.0-10.0	10	26	1.8	21.70	552	10.90	278	9.30	235	928	577
190/570R15	6.5 - 7.5	7	20	1.4	22.60	574	8.25	210	7.75	197	892	558
250/570R15	10.0 - 11.0	10	20	1.4	22.60	574	11.40	290	9.70	246	892	554
275/570R15	10.0-11.0	10	20	1.4	22.60	573	11.40	290	10.70	272	894	556
205/580R15	7.0 - 8.0	7	29	2	22.83	580	8.58	218	8.19	208	883	549
225/580R15	8.0 - 9.0	8	29	2	22.83	580	9.57	243	9.06	230	883	549
210/600R15	9.0- 11.0	10	20	1.4	23.50	597	10.90	278	7.90	200	858	533
225/600R15	10.0 - 11.0	10	20	1.4	23.70	602	10.40	264	8.30	211	851	529
240/600R15	10.0 - 11.0	10	20	1.4	23.50	598	10.60	268	8.70	222	857	532
330/620R15	14.0 - 16.0	15	20	1.4	24.40	620	15.55	395	13.22	336	826	514
255/635R15	10.0 - 11.0	10	22	1.5	25.24	641	11.61	295	9.72	247	799	497
290/700R15	9.0 - 11.0	9	35	2.5	27.70	704	12.80	325	11.20	285	723	452
290/710R15	9.0 - 11.0	9	35	2.5	28.10	714	12.70	322	11.20	285	713	445
350/720R15	14.0 - 15.0	14	22	1.5	28.31	719	16.26	413	13.86	352	712	443
<b>16" Diameter</b>												
Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
205/580R16	7.0 - 8.0	7	29	2	22.80	579	8.35	212	8.07	205	885	550
210/600R16	7.0 - 8.5	7	20	1.4	23.60	599	8.60	218	7.60	193	854	531
230/600R16	8.0 - 10.0	8	20	1.4	23.60	600	9.00	228	8.00	204	854	531
240/600R16	8.0 - 10.0	9.5	20	1.4	23.60	599	10.43	265	9.40	245	854	531
265/600R16	10.0 - 12.0	10.75	20	1.4	23.60	599	11.40	290	10.30	262	855	531
300/610R16	10.0 - 12.0	10.75	20	1.4	24.30	618	12.60	319	12.50	318	829	515
<b>17" Diameter</b>												
Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
205/610R17	7.0 - 8.0	8	29	2	24.50	622	8.50	215	7.90	201	823	512
215/610R17	7.0 - 8.0	8	29	2	24.30	618	9.00	229	9.00	229	829	515
210/620R17	7.0 - 8.0	7.5	20	1.4	24.20	615	9.00	229	8.25	210	833	518
230/620R17	8.5 - 9.5	9	20	1.4	24.38	619	9.80	249	8.99	228	827	514
250/620R17	9.5 - 10.5	10	20	1.4	24.35	618	11.00	279	10.00	254	828	515
210/635R17	7.0 - 8.0	8	20	1.4	25.00	635	9.10	230	8.10	205	807	501
240/635R17	8.5 - 9.5	9	20	1.4	25.20	640	9.90	251	9.25	235	800	497
255/635R17	9.5 - 10.5	10	20	1.4	25.20	640	10.75	273	9.90	251	800	497
275/635R17	10.5 - 11.5	11	20	1.4	25.20	640	11.60	295	10.50	267	800	497
290/645R17	9.0 - 11.0	10	20	1.4	25.60	649	11.80	300	12.20	311	789	490

**18" Diameter**

Tyre Size	Rim Choice	Rim Used	Measured at		Diameter		Section		Tread		Revolutions	
			psi	bar	ins	mm	ins	mm	ins	mm	mile	km
210/635R18	7.0 - 8.0	8.3	20	1.4	25.20	640	9.00	229	8.25	210	800	497
225/635R18	7.5 - 8.5	8.3	20	1.4	25.20	640	9.25	235	8.50	216	800	497
240/635R18	8.5 - 9.5	9	20	1.4	25.20	640	9.90	251	9.25	235	800	497
255/635R18	9.5 - 10.5	10	20	1.4	25.20	640	10.75	273	9.90	251	800	497
275/635R18	10.5 - 11.5	11	20	1.4	25.20	640	11.60	295	10.50	267	800	497
225/640R18	8.0 - 9.0	9	29	2	25.50	648	10.10	257	8.80	223	790	491
240/640R18	9.0 - 11.0	10	29	2	25.50	648	10.50	267	9.60	244	790	491
250/640R18	10.0 - 11.0	10	29	2	25.50	648	10.90	278	9.80	250	790	491
275/645R18	10.0 - 11.0	11	29	2	25.40	646	11.60	294	10.60	270	793	493
285/645R18	11.0 - 12.0	11	29	2	25.50	647	11.70	297	10.90	278	792	492
300/645R18	11.0 - 12.0	12	20	1.4	25.55	649	12.70	323	11.50	292	789	490
320/645R18	11.5 - 13.0	13	20	1.4	25.55	649	13.70	348	12.50	318	789	490
335/645R18	TBC											
255/660R18	10.0 - 11.0	11	29	2	26.00	660	11.00	279	9.80	248	776	482
270/680R18	10.0 - 12.0	11	20	1.4	26.90	683	11.75	298	10.30	262	750	466
285/680R18	11.0 - 12.0	11	29	2	27.00	685	11.90	302	11.00	280	748	465
270/690R18	10.5 - 11.5	11	20	1.4	27.15	690	11.90	302	10.50	267	743	462
320/690R18	12.5 - 13.5	13	20	1.4	27.15	690	13.90	353	12.50	318	743	464
280/705R18	10.0 - 12.0	11	29	2	27.80	706	12.00	304	10.60	270	726	451
300/705R18	11.0 - 13.0	13	29	2	27.80	705	13.70	348	12.00	305	727	452
320/705R18	12.5 - 13.5	13	29	2	27.80	706	13.90	353	12.60	320	726	451
365/720R18	14.5 - 16.0	14.5	20	1.4	28.39	721	15.94	405	14.37	365	710	441